

Rotary mower

Rotary mower with side discharge - Hydr. cutting height adjustment & Tilt-up

FRS 1500-1800 M / H



- Frontmounted, side discharge to the right
- Hydraulic cutting height adjustment
- Hydraulic tilt-up and water jacks for easy cleaning and service
- M - mechanical operated incl. PTO shaft
- H - hydraulic operated incl. hoses and quick couplings.



Technical data



Gator 3-in-1 knife



Mulching kit

Mechanical operated	FRS 1500 M / FRS 1500 H	FRS 1800 M / FRS 1800 H
Largest width	1945 mm (Side discharge) / 1915 mm (Collector)	2190 mm (Side discharge) / 2160 mm (Collector)
Largest length *	1590 mm	1630 mm
Largest height	750 mm	
Cutting width	1535 mm	1780 mm
Cutting height adjustment - stepless	30-80 mm	
Cutting height adjustment	Hydraulic	
Hydr. Tilt-up	Standard	
Number of rotors	3 pcs	
Number of knives	3 pcs	
Wheels	4 pcs 10 x 3"	
Power requirements	15 kW (21 HP)	20 kW (27 HP)
Capacity at 4 km/h	5100 m ² /h	6120 m ² /h
Capacity at 10 km/h	12750 m ² /h	15300 m ² /h
Weight *	295 kg	320 kg

* Length and weight depend on frame type

GMR

GMR maskiner a/s
DK-8700 Horsens
T. +45 75 64 36 11
www.gmr.dk

NESBO A/S
DK-9550 Mariager
T. +45 98 58 44 00
www.nesbo.dk

Dealer: