

Rotary mower

Rotary mower - Model Triplex with wide rear discharge

Model

THM 2500 - 3000 - hydraulic/mechanical

TH 2500 - 3000 - full hydraulic



- Front mounted
- Mechanical cutting height adjustment
- Mechanical / hydraulic operated or full hydraulic operated
- Hydraulic Tilt-up for easy maintenance and cleaning
- 5 fixed knives
- Great in work - small in transport



Technical data



Anti scalp disc



Transport position



Shut-off valve



Hydraulic system

Model	TH / THM 2500	TH / THM 3000
Largest width	2535 mm	2975 mm
Transport width	1750 mm	2000 mm
Largest length *	1550 mm	1655 mm
Largest height	500 mm	
Transport height	820 mm	920 mm
Cutting width	2480 mm	2900 mm
Cutting height	30 - 80 mm	
Cutting height adjustment	Mechanical	
Hydr. Tilt-up	Standard	
Number of rotors	5 pcs	
Number of knives	5 pcs (533 mm)	5 pcs (620 mm)
Wheels	6 pcs 10 x 3" air rubber wheels	
Necessary flow	60 liter / 250 bar	70 liter / 250 bar
Power requirements	25 kW (34 HP)	30 kW (41 HP)
Weight *	365 kg	440 kg

* Length and weight depend on frame type

GMR



GMR maskiner a/s
DK-8700 Horsens
T. +45 75 64 36 11
www.gmr.dk

NESBO A/S
DK-9550 Mariager
T. +45 98 58 44 00
www.nesbo.dk

Dealer: