

Rotary mower

Rotary mower

- Model Triplex with wide rear discharge

Model

THM 3500 - 4000 mekanical/hydraulic

TH 3500 - 4000 full hydraulic



- Front mounted
- Mechanical cutting height adjustment
- Full hydraulic or mechanical/hydraulic operated
- 7 fixed special knives
- Hydraulic Tilt-up for easy maintenance and cleaning
- Great in work - small in transport



Technical data



Shut-off valve



Transport position



Hydraulic Tilt Up



Gator 3-in-1 knife

Model	TH / THM 3500	TH / THM 4000
Largest width	3525 mm	4120 mm
Transport width	1750 mm	2000 mm
Largest length *	1625 mm	1735 mm
Largest height	600 mm	
Transport height	1200 mm	1450 mm
Cutting width	3460 mm	4025 mm
Cutting height	30 - 80 mm	
Cutting height adjustment	Mechanical	
Hydr. Tilt-up	Standard	
Number of rotors	7	
Number of knives	7	
Wheels	8 pcs 11 x 7" air rubber wheels	
Necessary flow	80 liter / 250 bar	85 liter / 300 bar
Power requirements	37,5 kW (51 HP)	41,5 kW (56 HP)
Weight *	520 kg	600 kg

* Length and weight depend on frame type

GMR

GMR maskiner a/s
DK-8700 Horsens
T. +45 75 64 36 11
www.gmr.dk

NESBO A/S
DK-9550 Mariager
T. +45 98 58 44 00
www.nesbo.dk

Dealer: