

Hydraulic transmissions

Hydraulic transmissions
- gear or piston pump systems

Model HT - F / V



- Available with
 - pistons pumps
 - servo-controlledpiston pump
 - electric oil cooler
- Specially adapted oil tanks

- Suction- and return filter
- Pressure limiting valve and reversing





Technical data

HT 45 F

With internal gear pump mounted under tractor and oil tank unit, suction- and return filter.

Pressure limiting valve and reversing.

HT 65 F / V

Fest mounted gear pump and speed-up gear on rear PTO of tractor, Oli tank mounted under tractor, return- and suction filter.

Pressure limiting valve and reversing.



HT 85 F / V

Fest mounted gear pump and speed-up gear on rear PTO of tractor Oil tank mounted under tractor, return and suction filter.

Pressure limiting valve and reversing.

HT 85 F 3-punkt

3-point mounted hydraulic transmission unit.

PTO-driven.

Adapted to agricultural Tractors.



Model	HT 45 F For tractors up to 35 hp	HT 65 F / V	HT 85 F / V	HT 85 F 3-point
Flow / litres / min	45 liter	65 liter	85 liter	
Operating pressure	180 bar	220 bar		
Weight	100 kg	120 kg 150 kg		150 kg



Dealer:	"/