

Rotary mower

Rotary mower - light model with rear discharge

Type FR 1300 - 1500 - 1800

LM mechanical driven - LH hydraulic driven



- Frontmounted
- Mechanical or hydraulic driven
- With hydraulic or mechanical adjustment of cutting height
- With hydraulic tilt-up
- 3 pcs. of special knives
- Rear discharge - wide spreaded
- Minimal maintenance

Technical data

	FR LM - LH 1300	FR LM - LH 1500	FR LM - LH 1800
Largest width	1370 mm	1670 mm	1930 mm
Largest length	1220 mm	1350 mm	1400 mm
Largest height	500 mm	700 mm	700 mm
Effective cutting width	1295 mm	1530 mm	1780 mm
Weight	170 kgs	265 kgs	285 kgs
Minimum need of power	16 HP / 12 kW	19 HP / 14 kW	21 HP / 15 kW
Number of rotors	3	3	3
Number of knives	3	3	3
Number of rubber wheels	4 pcs. 8 x 2,5" revolable	4 pcs. revolable	4 pcs. revolable
LM - mechanical driven LH - hydraulic driven	- via PTO shaft and V belt draw - from the tractors hydraulic system via V belt draw		
Height adjustment continuously variable	20 - 80 mm	30 - 90 mm	
Tilt-up	Hydraulisk to 65° from seat of tractor		

Additional equipment:



GMR

GMR maskiner a/s
Saturnvej 17 - DK 8700 Horsens

Phone +45 7564 3611
Fax +45 75645320
www.gmr.dk
stensballe@gmr.dk



Dealer: