

Flail Mower

Flail Mower easy model

SK 1300 - 1500 - 1700 MH / MM



- Hydraulic drive
- Front mounting
- Hydraulic side shift (options)
- Strong suction
- Rear roller with hydraulic height adjustment (options)
- Supporting leg (for storage)
- Stable at 2500 rpm
- Stable blades
- Rubber skirt to prevent stone ejection

Technical data

	SK 1300 MH	SK 1500 MH	SK 1700 MH	SK 1300 MM	SK 1500 MM	SK 1700 MM
Width	1575 mm	1775 mm	1975 mm	1575 mm	1775 mm	1975 mm
Length	1125 mm					
Height	875 mm					
Cutting width	1300 mm	1500 mm	1700 mm	1500 mm	2000 mm	2200 mm
Type of flails	Y or J flails					
No. of Y flails	84 sets.	96 sets.	108 sets.	84 sets.	96 sets.	108 sets.
No. of J flails	42 sets.	48 sets.	54 sets.	42 sets.	48 sets.	54 sets.
Hydraulic side shift	300 mm	400 mm	400 mm	400 mm	500 mm	500 mm
Height adjustment	15 - 75 mm					
Power requirements	12 kW (16 HK)	14 kW (19 HK)	15 kW (21 HK)	12 kW (16 HK)	14 kW (19 HK)	15 kW (21 HK)
Weight	335 kg	375 kg	415 kg	335 kg	375 kg	415 kg



GMR

GMR maskiner a/s
Saturnvej 17 - DK 8700 Horsens

Phone +45 7564 3611
Fax +45 75645320
www.gmr.dk
stensballe@gmr.dk



Dealer: