## Rotary mower

Rotary mower Triplex

Type THM 3500 - 4000 - hydraulic/mechanical Type TH 3500 - 4000 - hydraulic\_\_\_\_\_



- Frontmounted
- Mechanical adjustment of cutting height
- Mechanical/hydraulic or full hydraulic driven
- Hydraulic tilt-up as standard equipment
- 7 fixed special or Gator knives
- Large in work small in transport



## Technical data

	THM / TH 3500	THM / TH 4000
Largest width	3530 mm	4070 mm
Transport width	1900 mm	2000 mm
Largest length	1600 mm	1600 mm
Largest height	600 mm	600 mm
Transport height	1200 mm	1450 mm
Cutting width	3470 mm	4025 mm
Cutting height	20-80 mm	20-80 mm
Height adjustment	mechanical	mechanical
Hydraulic tilt-up	standard	standard
Numbers of rotors	7	7
Number of special knives	7	7
Revolving airfilled rubber wheels	8	8
Need of power	37,5 kW / 51 HP	41,5 kW / 56 HP
Weight	520 kg	600 kg
Necessary flow	80 liters at 250 bar	90 liters at 300 bar
Side mowers	- independently to be tipped to vertical - declutch automatically when lifted more than 400 mm - cuts 10° below level and 15° above level compared to the center mower	
Transmission	mechanical via V-belt drive/hydraulic via direct drive	
Drive type mechanical THM	center mower - mechanical side mower - hydraulic from tractors external hydraulic system	
Drive type hydraulic TH	full hydraulic driven from the tractors hydraulic system	









Dealer: